

## **SUBSTITUTION TABLE LVL 16 TO HYNE BEAM 15**



Hyne Beam 15 is the perfect choice for long spanning beams.and lintels. Glulam offers a number of benefits over other engineered alternatives such as:

Available ex stock Supplied in 0.6m increments H3.1 Treated Pre-Cambered as standard

The below LVL 16 conversion table has been engineered to offer the best performing alternative using Beam 15. The size options below are at least as good as the original beam in all beam applications.

Performance of the Beam 15 substitution is subject to the original beam member being designed appropriately.

When depth space is limited in applications such as midfloor beams, 130mm wide Beam 15 is available also.

Beam 15 Conversion chart:	
LVL 16 Size	85mm Beam 15
200 x 90	195 x 85
240 x 90	260 x 85
300 x 90	295 x 85
360 x 90	360 x 85
400 x 90	395 x 85

For additional design applications utilising Beam 15 download the Hyne Design (HD7) software from the IBuilt website.

www.ibuilt.co.nz







149 Kerrs Rd, Wiri, Auckland



PO Box 76412, Manukau, Auckland 2241, New Zealand



Tech Info Line: 0800-022-352



Phone: +64-9-268 6540



sales@nzwoodproducts.co.nz techinfo@nzwoodproducts.co.nz



www.nzwoodproducts.co.nz www.ibuilt.co.nz